ENVIROSEAL LAS-320™

ENVIROSEAL LAS-320™ asphalt sealer/ preservative is not a petroleum based product. It is a blended polymeric liquid that forms a molecular bond with the oxidized asphalt surface and penetrates cracks and raveled areas.

UV and water are the two primary reasons for asphalt failure. **LAS-320™** makes the surface impervious to water eliminating freeze/thaw damages and repels most common chemicals, including petroleum and acids. Powerful UV inhibitors are added to increase the lifecycle and it can be used on both new or old asphalt.

ENVIROSEAL LAS-320™ has undergone field testing by USAF at McGuire AFB in New Jersey



and by the
FAA which
has classified
it as a Fuel
Resistant
Coating. Test
results are
available upon
request.







ENVIROSEAL LAS-320™ was evaluated as a fuel resistant as a Fuel Resistant sealer as part of the FAA and U.S. Air Force Study on "*Rejuvenators*, *Rejuvenator/Sealers and Seal Coats for Airfield Pavements*".

ENVIROSEAL LAS-320™ was developed for use on asphalt pavement surfaces including airport aprons, fuel storage areas, parking lots and commercial/industrial driveways. Some added benefits are low VOC and no odor making it ideal for public parking areas like hospitals, schools, or other institutions.



UNTREATED TREATED



ENVIROSEAL LAS-320™ is easy to use and cleans up with water. It can be brushed or sprayed and has a coverage rate of 100 square feet per gallon (2.5 liters/M2)

ENVIROSEAL LAS-320™ dries quickly, usually <u>less than one hour</u> and can be striped when dry

ENVIROSEAL LAS-320™ is Eco-Friendly does not track and has very little odor

ENVIROSEAL LAS-320™ is available in

- * 5-gallon Pails
- * 55 gallon Drums
- * 275 gallon Totes




PRESERVE YOUR ASPHALT ENVIROSEAL LAS-320™

- Approved as a Fuel Resistant Asphalt Sealer by the FAA
- Eliminates damage from UV and water
- Repels most all liquids and Eliminates destruction caused by petroleum spills
- VOC Rating less than 100 grams/liter
- ♦ Non-Toxic, Non-Hazardous
- Prevents potholes caused by freezing
- Increases asphalt life by several years
- Exceeds ASTM Standards for asphalt emulsion products.
- Used and approved by the U.S. Air Force and NATO in airfield applications
- Ideal for use in shopping centers, truck stops, gas stations, parking lots, fuel storage, and secondary containment
- Easy application, Can be applied with a brush or spray
 — Water Clean-Up
- No Odor and does not track
- Dries in less than an hour
- Coverage rates average 100 square feet per gallon (2.5 liters/M2)
- LAS-320 is available in Concentrate for commercial and industrial applications



- * COMMERCIAL
- * INDUSTRIAL
- * RESIDENTIAL



Enviroseal

LAS-320™

1019 SE Holbrook Court Port St. Lucie, FL 34952 Phone: 772-335-8225

sales@enviroseal.com WWW.ENVIROSEAL.COM

Enviroseal

LAS-320TM

Asphalt Sealer/ Preservative



ENVIROSEAL LAS-320™ preserves your asphalt

Enviroseal LAS-320™ is an environmentally safe asphalt sealer preservative that can be quickly and easily applied to increase the life of asphalt. It protects against petroleum and UV damage and repels most liquids. This protective barrier prevents water seepage which causes sub-base failure that results in potholes.

Low VOC

Environmentally Safe