

Enviroseal Corporation
1019 SE Holbrook Ct
Port St. Lucie, FL 34952
PHONE: 772-335-8225
sales@enviroseal.com
www.enviroseal.com



DURASEAL PLUS™

SURFACE PREPARATION

- **Read instructions prior to use**
- **Clean surface area to remove all foreign matter.**
- **Do not apply to concrete less than 30 days old.**
- **Do not apply over previously treated surfaces without removing old paint/sealer from surface and allow to dry.**

APPLICATION

One saturation coat is normally sufficient for vertical, smooth dense concrete or masonry. For textured or horizontal surfaces a second coat may be required. A second coat should only be applied wet on wet before the first coat dries.

COVERAGE

50 –400 square feet/gallon (1.2 to 10 square meters/liter)
Due to porosity and texture, some surfaces may require additional applications. Always test a small area to determine actual coverage rate and satisfaction of appearance. Coverage rate will vary based on surface porosity.

CLEAN UP

Clean hands and tools with soapy water. Clean drips, runs and over-spray residue while still wet, using detergent and water

IMPORTANT NOTE

Always test a small area to verify satisfaction and appearance

**5-Gallons
(18.92 Liters)**

KEEP FROM FREEZING

REFER TO SDS FOR ADDITIONAL INFORMATION

WARNING! KEEP OUT OF REACH OF CHILDREN

READ AND UNDERSTAND ALL INSTRUCTIONS PRIOR TO USE