



## LAS-320™

## TECHNICAL DATA SHEET



## Eco-Friendly Asphalt Sealer

**Description:** LAS-320™ is a polymeric based fuel resistant asphalt sealer developed to protect asphalt from accidental and premature degradation. It makes a molecular bond with oxidized surfaces and penetrates cracks and eruptions. LAS-320™ makes the surface impervious to water and is chemical resistant.

**Easy to Apply:** Simply pour LAS-320™ on the surface and spread liberally with a push broom or paint roller. Approximate coverage is 80 to 100 square feet per gallon depending on surface condition. Work the LAS-320™ thoroughly into the asphalt surface and brush out all puddles. **Crack Repairs:** Fill cracks ½" or less with sand before application and pour LAS-320™ into the crack thoroughly soaking the sand. Broom out excess material.

- ✓ **Classified as a Fuel Resistant Sealer by the FAA**
- ✓ **Low VOC Rating 94 Grams per Liter**
- ✓ **Environmentally safe – No PAH**
- ✓ **No odor and No tracking**
- ✓ **Repels most liquids and chemicals**
- ✓ **Eliminates HMA degradation and UV damage**
- ✓ **Non-toxic - Non-hazardous - Non-flammable**
- ✓ **Dries quickly- usually less than 30 minutes**
- ✓ **Can be applied with a broom or sprayed**
- ✓ **Coverage rate +/- 100 square feet per gallon**

Contact us for technical assistance  
1-800-775-9474 or visit [www.enviroseal.com](http://www.enviroseal.com)

### LAS-320™ Will

**Protect** Asphalt surfaces from degradation caused by UV or chemical spills.

**Preserve** The integrity of asphalt to seal the exposed surface

**Provide** Resistance to the effects of weathering and oxidization



### Easy to Apply

#### Formulation Constants

Non-Volatile Solids	+/- 25%
Density	+/- 8.5 (1.019 kg/l)
VOC grams/liter	94 g/l
Ph	+/- 8

#### PACKAGING

5-Gallons  
55-Gallons  
275-Gallons

#### Manufactured in USA by

Enviroseal Corp.  
1019 SE Holbrook Ct.  
Port St. Lucie, FL, 34952  
[sales@enviroseal.com](mailto:sales@enviroseal.com)  
Phone: 772-335-8225  
[www.enviroseal.com](http://www.enviroseal.com)